

imageRUNNER iR3035 / iR3045

Specifications

TYPE:	DIGITAL, MULTIFUNCTION IMAGING SYSTEM
Imaging System:	Laser Dry Electrostatic Transfer
Developing System:	Dry Mono Component Developing System
Fixing System:	On-Demand
Image Server Memory:	Standard 512MB RAM/20GB HDD
First-copy Time:	Approx. 3.9 Seconds from Platen Glass
Warm-up Time:	Approx. 10 Seconds from Sleep Mode Approx. 30 Seconds from Main Power Off
Copy/Print Speed:	35/45 ppm (A4)
Max. Mail Boxes Supported:	100
Max. Copy Reservation:	5 Jobs
Resolution:	
Scan:	600 dpi x 600 dpi
Print:	2400 dpi x 600 dpi (equivalent)
Copy:	1200 x 600
Halftone:	256 Gradations of Gray
Duplexing:	Standard Automatic Trayless Duplexing
Magnification Reduction/ Enlargement:	25% to 400% – Platen 25% to 200% – Feeder (in 1% increments)
Exposure Control:	Automatic or Manual (9 Levels)
Paper Sources	
Standard:	Dual 550-sheet Paper Cassettes (1,100 Sheets) Stack Bypass (50 Sheets)
Optional:	2,500-sheet Paper Deck Dual 550-sheet Cassette Feeding Unit Max. total = 4,750 sheets
Multiple Copies:	1 to 9,999
Paper Weights:	64–90gsm (Cassette) 64–128gsm (Stack Bypass)
Network Interface	
Connections:	10/100Base-T (RJ-45)
Dimensions (H x W x D):	761mm x 565mm x 700mm
Installation Space: (W x D):	930mm x 115mm
Weight:	116kg
Power Requirements:	230V/6a/50Hz
Power Consumption:	1.35kW (Max.)
Drum:	Organic Photo Conductor (OPC) – Estimated Yield: 75,000 Impressions
Toner Yield:	24,000 @ 6% Coverage
DUPLEXING AUTOMATIC DOCUMENT FEEDER-N1	
Acceptable Originals:	A5R-A3
Capacity:	50 Sheets (80gsm)
Max. Paper Weight:	64–128gsm
INNER 2-WAY TRAY-D1 (OPTION)	
Number of Trays:	1 Tray
Tray Capacity:	
Lower Output Tray (Standard):	250 Sheets (A4)

Upper Output Tray:	100 Sheets (Other Sizes)
100 Sheets (A4)	
50 Sheets (Other Sizes)	
Acceptable Paper Sizes:	A5R-A3
Attachable Accessories:	Copy Tray-J1
FINISHER-S1 (OPTION)	
Number of Trays:	1 Tray (2nd Tray Optional)
Tray Capacity	
Non-collate, Collate,	
Group Mode:	1,000 Sheets (A4)
Staple Mode:	1,000 Sheets/30 Sets
FINISHER TRAY-B1 (OPTION FOR FINISHER S1)	
Tray Capacity:	300 sheets (A4) Per tray 150 sheets (A3) Per tray
FINISHER-S1 TRAY CAPACITY WITH ADDITIONAL FINISHER TRAY-B1	
Non-collate, Collate	600 A4-300 A3
Group Mode:	300 Sheets per Tray (A4)
Staple Mode:	300 Sheets/30 Sets per Tray (A4) 150 Sheets/30 Sets (A3)
Staple Position/Size:	Corner Stapling (A4-A3)
Max. Stapling Capacity (Up to 80gsm. Bond):	50 Sheets (A4)
Attachable Accessories:	Puncher Unit-R1, Q1, S1
COPY TRAY-J1 (OPTION FOR INNER 2-WAY TRAY-D1 OR FINISHER-S1)	
	150 sheets (A4) 75 sheets (A3)
FINISHER-AE1/SADDLE FINISHER-AE2 (OPTION)	
Number of Trays:	2 Trays
Tray Capacity	
Non-collate, Collate, and Group Mode:	1,000 Sheets (A4) 500 Sheets (A3)
Staple Mode:	1,000 Sheets/30 Sets (A4) 500 Sheets/30 Sets (A3)
Max. Stapling Capacity	
Corner, Double:	50 Sheets (A4), 30 Sheets (A3)
Saddle-stitching	(Available on Saddle Finisher-Q4 Only)
Acceptable Paper Sizes:	A4R-A3
Capacity/Tray:	1 to 5 Sheets/25 Sets 6 to 10 Sheets/15 Sets 11 to 15 Sheets/10 Sets
Max. Stapling Capacity/Set:	15 Sheets
Folding:	V-fold
Attachable Accessories:	Puncher Unit- M1B,L1B,N1C
CASSETTE FEEDING UNIT-Y3 (OPTION)	
Paper Capacity:	Dual 550-sheet Paper Cassettes (1,100 Sheets/80gsm)
Acceptable Paper Sizes:	A5R-A3
Acceptable Paper Weights:	64–90gsm

PAPER DECK-Q1 (OPTION)

Paper Deck Capacity:	2,500 Sheets (80gsm)
Paper Size:	A4
Acceptable Paper Weights:	64–90gsm

MULTI-PDL PRINTER KIT-S1 (OPTION)

Processor:	Canon Custom Processor–Shared RAM: 512MB–Shared
Hard Disk:	20GB–Shared
PDL Support:	PCL 5e, PCL 6, PostScript 3 Emulation, UFR II

INTERFACE CONNECTIONS

Standard:	RJ-45 (10/100Base-T), USB 2.0 High-speed
Network OS:	Windows® 98/Me/2000/XP Windows NT® 4.0/Server 2003 Macintosh® OS 8.0 or Later (PPD) Solaris™ 1.1x, 2.5x or Later Novell® NetWare® v3.2, 4.1, 4.11, 4.2, 5, 5.1, 6, 6.5 (IPX/SPX™)

UNIVERSAL SEND KIT-B1 (OPTION)

Sending Methods:	E-mail, iFAX, Super G3 Fax (Optional), User Inbox, File Server (IPX, FTP, SMB)
Address Book Capacity:	Max. 1,800 Destinations Max. 5 LDAP Servers
File Format:	MTIFF, TIFF, PDF, Optional PDF (OCR)

SUPER G3 FAX BOARD-Q1 (OPTION)

Applicable Line:	Public Switched Telephone
Network (PSTN)	
Connection Lines:	One
Sending/Original Sizes:	A5R-A3 (from Document Feeder)
Recording/Printing Sizes:	A5R-A3
Compression System:	MMR, MR, MH, JBIG
Auto Dial Function:	Address Book: 1,800 Destinations (Total)
Image Memory:	Approx. 3,700 pages (Sourced from HDD)
Max. Confidential Fax Inboxes:	100

ADDITIONAL OPTIONAL ACCESSORIES AND UTILITIES

Platen Cover Type H	Puncher Unit-L1B,M1B,N1C
Pedestal	Document Tray-J1
Copy Tray-J1	Card Sets
Card Reader-C1	Secure PDF Kit- A1
Universal Send Kit G1	Envelope Feeder Attachment-C1
Searchable PDF Kit A1	HDD Erase kit - A1
Barcode Printing Kit - A1	Encrypted Printing Kit - C1
Secure Watermark Kit - A1	HDD Encryption kit - B4
Signature PDF kit - A1	
Web Access Software Kit - F1	
Voice Guidance Kit - A1	
Voice Operation Kit - B1	
DADF Access Handle - A1	
Remote Operator Kit - A2	
256 MB Memory Expansion	